

Kohlendioxid (CO₂) gefüllte Einweg-Gaszylinder

Füllgewicht CO ₂ [g]	Wasserkapazität [ml]	Durchmesser [mm]	Gesamtlänge [mm]	Halsausführung
7,5	10	18,0	65,0	ø8,7mm
8	10	18,0	65,7	¾-24 UNF-1A
10	14	18,6	82,9	¾-24 UNF-1A
10	14	18,65	83,0	¾-24 UNF-1A
11	14	18,6	83,0	ø7,3mm
11	14	18,6	83,0	¾-24 UNF-1A
10,5	15	18,6	82,5	ø8,7mm
16	21	22,0	88,4	ø8,85mm
15 & 16	21	22,0	88,2	ø8,7mm
16	21	22,0	86,4	ø8,3mm
15 & 16	21	22,0	88,4	¾-24 UNF-1A
16	21	22,0	88,6	¾-24 UNF-1A
16	22	22,0	90,4	ø8,85mm
16	22	22,0	94,4	¾-24 UNF-1A
18, 20, 23, & 24	32	25,4	107,0	½-20 UNF-1A
24,5	33	25,4	107,0	¾-24 UNF-1A
28	40	20,7	160,0	ø8,7mm
28	40	20,7	162,0	¾-24 UNF-1A
28, 30 & 33	45	25,4	139,0	½-20 UNF-1A
30	52	30,0	121,0	½-20 UNF-2A
30, 35, 36 & 38	52	30,0	121,0	½-20 UNF-1A
35	52	30,0	121,0	½-20 UNF-2A
38	52	30,0	121,0	¾-24 UNF-1A
38, 40 & 45	63	30,0	141,0	½-20 UNF-1A
55, 56 & 60	85	31,8	164,0	½-20 UNF-1A
75	103	31,8	193,5	½-20 UNF-1A
84	115	35,0	185,0	½-20 UNF-1A
86	120	35,0	196,0	½-20 UNF-1A
120 & 135*	210	50,0	182,0	½-20 UNF-1A
120, 135 & 150	210	50,0	179,0	½-20 UNF-1A
215	300	50,0	244,0	½-20 UNF-1A
230*	350	50,0	275,0	½-20 UNF-1A
255 & 295	400	60,0	226,0	½-20 UNF-1A
250*	400	60,0	235,0	½-20 UNF-1A
310	420	50,0	309,0	½-20 UNF-1A
315	440	50,0	328,0	½-20 UNF-1A
290*	450	60,0	255,0	½-20 UNF-1A
355	490	60,0	265,0	½-20 UNF-1A
330*	500	50,0	375,0	½-20 UNF-1A
460	620	60,0	321,0	½-20 UNF-1A
460*	700	60,0	368,0	½-20 UNF-1A

* DOT zugelassen